

Spirit of Quality & Service



श्री
Shri Hari
Machinery

SALIENT FEATURES

- No container no crown arrangement.
- Single motor synchronizes conveyor, star wheel, & platform turret.
- Adjustable height of conveyor belt.
- All contact parts are made out of stainless steel.
- Pick & Place arrangement.
- Torque adjustable.
- Low noise level, low power consumptions.
- No bottle no crown.
- Outside no crown machine stop.

Technical specification :

Model	ASCM-100
Output/Hour	1800
Direction of Machine*	Left to Right
No. of Head	1 Nos.
Electrical** Main Motor	1.5 HP / 415 Volts / 50 Hz.
Specification Cap Feeding Vibrator	300 Watt.
Height of Conveyor**	860 mm to 910 mm

Automatic Measuring/Dosing Cup Placement & Pressing Machine



SALIENT FEATURES

- High Production Speeds.
- Stainless Steel 304 construction.
- GMP design.
- Accurate lable placement.
- Full Security Package including counter.
- Product data storage facility.
- No change parts requirements.
- Very less down time for change over.
- Suitable for Glass, Plastic, Pet, Tin, Corrugated containers.

Technical specification :

Model	ASAL-150
Output/Hour	3600 to 9000 Nos.
Direction of Movement	Left to Right
Conveyor Motor	0.5 HP / 415 Volts / 50 Hz.
Electrical** Pressing Device Motor	0.5 HP / 220 Volts / 50 Hz.
Specification Sticker Roll Stepper Motor	6 V DC
Height of Conveyor**	860 mm to 910 mm

Automatic Single Head Crown Capping Machine



SALIENT FEATURES

- No container no cup arrangement.
- Single motor synchronizes conveyor belt, to align with other machine of the line.
- Adjustable height of conveyor belt, to align with other machine of the line.
- Low noise level, low power consumptions.
- Self lubricating UHMW-PE guide profile for low friction wear surface, smooth and noiseless conveying.
- SS cladding or hard chrome plating of all exposed parts to ensure long life and resistance against corrosion.
- Universal coupling for quick and easy setting of in-feed worm.

Technical specification :

Model	AMCPP-150
Output/Hour*	3600 to 9000
Direction of Movement	Left to Right
Electrical** Main Motor	0.75 HP / 220 Volts / 50 Hz.
Specification Cap Feeding Vibrator	300 Watt. Magnetic Coil
Height of Conveyor**	860 mm to 910 mm

Automatic Self Adhesive Vertical Labeling Machine



Rotary Bottle Washing Machine



SALIENT FEATURES

- $\pm 1\%$ Filling accuracy on single dose.
- No bottle No filling system
- Rigid vibration free construction for trouble free performance.
- S.S. Elegantly matt finished body.
- Minimum change overtime, from one size to another container or fill size.
- Self lubricating UHMW-PE guide profile for SS slat chain provides low friction wear surface, smooth and noiseless conveying.
- Pneumatic bottle stopping arrangement.
- Synchronized two nos. A.C. drive for main motor & conveyor belt.
- Safety guard for conveyor gear box, motor and pneumatic cylinders.
- Inbuilt protection against over current. Voltage fluctuation, Short circuit in.

Technical specification :

Model	ALF-100	ALF-150	ALF-200
Output/Hour*	2400 to 6000*	3600 to 9000*	5000 to 12000*
Direction of Machine*	Left to Right		
No. of Head/Syringe	4 Nos.	6 Nos.	8 Nos.
Fill Size**	5 ml to 100 ml		
Electrical** Main Machine	1 HP / 415 Volts / 50 Hz.		1.5 HP/415 Volts/50 Hz.
Specification Conveyor	0.5 HP / 415 Volts / 50 Hz.		
Height of Conveyor	860 mm to 910 mm adjustable		

Automatic Multi Head Ropp Cap Sealing Machine



SALIENT FEATURES

- Geneva Mechanism.
- Four Inner & one outer.
- Sequence of washes to customer's choice.
- Stationary nozzles eliminate contamination of water cycles.
- Individual solenoid valve for each washing sequence, that eliminates carbon plate and other accessories reduce leakage and maintenance to minimum.
- Higher capacity centrifugal pumps to wash bigger bottles (500 & 1000 ml.)
- Pumps and tanks are mounted on portable stand for easy maintenance.
- Bottle guid system especially for light weight bottle.
- Separate panel control to avoid any short circuit due to spraying of water.

Technical specification :

Model	ARWM-64	ARWM-96
Output/Hour*	2600 to 6000 Nos.	4300 to 9000 nos.
No. of Container Holder	64	96
Direction of Machine*	Clock Wise	
Electrical** Main Motor	0.5 HP / 415 Volts / 50 Hz.	
Specification Pump Two Nos.	1 HP x 2 = 2 HP 415 Volts / 50Hz.	
Electric Heater	3 Kw.	
Tank Capacity	75 Ltrs. S.S. 304 (2 Nos.)	
Wash Cycle	4 Inner + 1 Outer	
Working Height	860 to 910 mm	

Automatic Volumetric Liquid Bottle Filling Machine



SALIENT FEATURES

- No container no cap arrangement.
- S.S. Elegantly matt finished body.
- Adjustable height of conveyor belt, to align with other machine of the line.
- Sealing pressure can be varied to suit different gauges and size of caps.
- Self-lubricating UHMW-PE guide profile for low friction wears surface, smooth and noiseless conveying.
- SS cladding or hard chrome plating of all exposed parts to ensure long life and resistance against corrosion.
- Universal coupling for quick and easy setting of in-feed worm.
- Adjustable bottle height gauge for easy and quick setting.

Technical specification :

Model	ARCS-100	ARCS-150	ARCS-200
Output/Hour*	3600 to 6000	3600 to 9000*	4000 to 12000*
Direction of Machine*	Left to Right		
No. of Head	4 Nos.	6 Nos.	8 Nos.
Electrical** Main Machine	1.5 HP / 415 Volts / 50 Hz.		2 HP/415 Volts/50 Hz.
Specification Conveyor	0.25 HP / 415 Volts / 50 Hz.		
Height of Conveyor**	860 mm to 910 mm adjustable		

Rotary Rinsing, Filling and Capping Machine



SALIENT FEATURES

- Rotary neck holding.
- Air Blow Conveyor on the out feed.
- Slat Belt Conveyor on the out feed.
- Drive is on chain of gears (Not Indexing Cam) hence low on maintenance.
- Speed Control by AC Drive.
- Cap Elevator for feeding cap to the bowl with automatic operation.
- Speed indicator on main panel.
- Can handle all bottle size ranging from 200 up to 2000 ml.
- Stainless Steel enclosure provided for complete hygienic bottling.
- Easy openable nozzles for easy cleaning.
- Can handle bottles blown from low grammage Preforms without bottling.
- Can be linked directly to Automatic Blow Molding Machine for online Blow - Rinse - Fill - Seal.
- Compatible with Online Shrink Tunnel, Labeling Machine or Ink Jet Printer.

Technical specification :

Model	ARFC-60	
No. of Heads	16-12-6	
Capacity @ 1000 ml.	2700 BPH	
Power Consumption	4.23 KW	
Weight	2500 kgs.	
Bottle Size Range	200 to 2000 ml.	
Container Size**	Bottle Size	Diameter 50 mm to 100 mm.
	Caps Type	Respectively Height 150 mm to 320 mm
		4 Inner + 1 Outer

OUR OTHER PRODUCT

Turn Table Scrambler & Un-Scrambler



Online Visual Bottle Inspection Machine



Packing Conveyor Belt

